

## **EOSC 547:** **Tunnelling & Underground Design**

### **Topic 4:** **Hard Rock Tunnelling Methods**



1 of 40

Tunnelling Grad Class (2012)


Dr. Erik Eberhardt

## **Tunnel Excavation in Rock**

It is instructive to consider the fundamental objective of the excavation process - which is to remove rock material (either to create an opening or to obtain material for its inherent value). In order to remove part of a rock mass, it is necessary to induce additional fracturing and fragmentation of the rock.

This introduces three critical aspects of excavation:

- ➡ The peak strength of the rock must be exceeded.
- ➡ The *in situ* block size distribution must be changed to the required fragment size distribution.
- ➡ By what means should the required energy be introduced into the rock?




2 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Tunnel Excavation in Rock


### Strength



The tensile strength of rock is about  $1/10^{\text{th}}$  the compressive strength and the energy beneath the stress-strain curve is roughly its square. Therefore, breaking the rock in tension requires only  $1/100^{\text{th}}$  of the energy as that in compression.

### Block size

The fracturing of rock during excavation changes the natural block size distribution. The goal therefore is to consider how best to move from one curve to the other in the excavation process.



Hudson & Harrison (1997)



3 of 40

Tunnelling Grad Class (2012)



Dr. Erik Eberhardt

## Energy and Excavation Process

One objective in the excavation process may be to optimize the use of energy, i.e. the amount of energy required to remove a unit volume of rock (specific energy =  $\text{J/m}^3$ ). There are two fundamental ways of inputting energy into the rock for excavation:

➡ **Blasting:** Energy is input in large quantities over very short durations (cyclical - drill then blast, drill then blast, etc.).

➡ **Machine Excavation:** Energy is input in smaller quantities continuously.




4 of 40

Tunnelling Grad Class (2012)


Dr. Erik Eberhardt

## Drill & Blast

The technique of rock breakage using explosives involves **drilling blastholes** by percussive or rotary-percussive means, loading the boreholes with explosives and then **detonating** the explosive in each hole **in sequence** according to the blast design.



The explosion generates a **stress wave** and significant **gas pressure**. Following the **local fracturing** at the blasthole wall and the **spalling** of the free face, the subsequent **gas pressure** then provides the necessary energy to **disaggregate** the broken rock.



Hudson & Harrison (1997)




5 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Conventional Drill & Blast Cycle







6 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Drill & Blast - Drilling Rates



Thuro & Plinninger (2003)




7 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Drill & Blast - Drilling Rates



UNIT-NTH (1995)




8 of 40

Tunnelling Grad Class (2012)


Dr. Erik Eberhardt

## Blasting Rounds - Burn Cut

The correct design of a blast starts with the **first hole** to be detonated. In the case of a tunnel blast, the first requirement is to create a **void** into which rock broken by the blast can **expand**. This is generally achieved by a **wedge or burn cut** which is designed to create a clean void and to **eject** the rock originally contained in this void clear of the tunnel face.



Burn cut designs using millisecond delays.





9 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Blasting Rounds - Blast Pattern Design



10 of 40



Tunnelling Grad Class (2012)

Dr. Erik Eberhardt



## Specialized Blasting Techniques

During blasting, the **explosive damage** may not only occur according to the **blasting round design**, but there may also be extra rock damage **behind** the excavation boundary. To minimize damage to the rock, a smooth-wall blast may be used to create the final excavation surface.



Hudson & Harrison (1997)

The smooth-wall blast begins by creating a rough opening using a large bulk blast. This is followed by a smooth-wall blast along a series of closely spaced and lightly charged parallel holes, designed to create a fracture plane connecting the holes through by means of coalescing fractures.



11 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Blasting Accessories



Explosives



Delays: used to orchestrate rotational firing.



Primacord: ignition velocity is approx. 6,400 m/s.



Safety fuse: Gives miner time to light all fuses and still have time to seek safety before the blast occurs.



12 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Blasting Rounds - Fragmentation

How efficiently muck from a working tunnel or surface excavation can be removed is a function of the **blast fragmentation**. Broken rock by volume is usually **50% greater** than the *in situ* material. In mining, both the ore and waste has to be moved to surface for milling or disposal. Some waste material can be used underground to **backfill** mined voids. In tunnelling, everything has to be removed and dumped in fills - or if the material is right, may be removed and used for road ballast or concrete aggregate (which can sometimes then be re-used in the tunnel itself).




13 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Blasting - Summary




14 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanical Excavation in Rock

Tunnel Boring Machine (TBM)



15 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanical Excavation in Rock

There are two basic types of machine for underground rock excavation:



**Partial-face machines:** use a cutting head on the end of a movable boom (that itself may be track mounted).



**Full-face machines:** use a rotating head armed with cutters, which fills the tunnel cross-section completely, and thus almost always excavates circular tunnels.



16 of 40


Tunnelling Grad Class (2012)

Dr. Erik Eberhardt



## Mechanical Excavation in Rock

Partial-face machines are cheaper, smaller and much more flexible in operation.





17 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanical Excavation in Rock

Full-face machines - when used for relatively straight and long tunnels (>2 km) - permit high rates of advance in a smooth, automated construction operation.



18 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanical Excavation

The advance rate at which the excavation proceeds is a function of the **cutting rate** and **utilization factor** (which is the amount of time that the machine is cutting rock). Factors contributing to low utilization rates are difficulties with ground support and steering, the need to frequently replace cutters, blocked scoops, broken conveyors, etc.



The cutters may jam if the TBM is pushed forwards with too much force. Then they might scrape against the rock and become flattened on one side.



19 of 40



Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## TBM Operation

Factors that may control TBM performance include:

- TBM Penetration Rate (meters/machine hour)
- TBM Downtime (minutes)
- TBM Utilization (machine hours/shift hours)
- Tool Wear (tool changes per shift)




20 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanics of Rock Cutting

In tunnelling terms, a TBM applies both thrust ( $F_n$ ) and torque ( $F_t$ ) during the cutting process. In selecting the proper cutting tool, the engineer wishes to know how the tools should be configured on a machine cutting head, how to minimize the need to replace cutters, how to avoid damaging the cutter mounts, and how to minimize vibration.



Hudson & Harrison (1997)



21 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanics of Rock Cutting

Cutting involves a complex mixture of tensile, shear and compressive modes of failure. With thrust, the cutting disc penetrates the rock and generates extensive crack propagation to the free surface. Further strain relief occurs as the disc edge rolls out of its cut, inducing further tensile cracking and slabbing at the rock surface.



NTNU-Arleggsdrift (1998)

22 of 40



Tunnelling Grad Class (2012)

Dr. Erik Eberhardt



## Mechanics of Rock Cutting - Cutter Wear

The primary impact of disc wear on costs can be so severe that cutter costs are often considered as a separate item in bid preparation. In general, 1.5 hours are required for a single cutter change, and if several cutters are changed at one time, each may require 30-40 minutes. Even higher downtimes can be expected with large water inflows, which make cutter change activities more difficult and time-consuming.



23 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanical Excavation - Cutter Heads

**Delays:** When the tunnel boring machine is inside the tunnel, the cutters must be changed from the inside the cutting head.



24 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt



## Mechanical Excavation - Cutter Heads



25 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanical Excavation - Cutter Heads



26 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanical Excavation - Cutter Heads



27 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Mechanical Excavation - Cutter Heads



28 of 40



Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## TBM Excavation & Design

The two main factors that will stop tunnel boring machines are either the rock is too hard to cut or that the rock is too soft to sustain the reactionary force necessary to push the machine forward. TBM's will operate within certain ranges of rock deformability and strength, where the machine can be tailored to a specific range to achieve maximum efficiency (the risk being if rock conditions diverge from those the TBM is designed for).

Instability problems at the tunnel face, encountered during excavation of the 12.9km long Pinglin tunnel in Taiwan.



Barla & Pelizza (2000)



29 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## TBM Excavation & Design

Table 1 : General classification scheme for tunnelling machines (AITES / ITA, Working Group No.14).

| Support         |        | Excavation                             |  | Machine  |                      |
|-----------------|--------|--|--|--|----------------------|
| Location        | System | Method                                 | Tool   | Reaction Force   | Category             |
| Cavity          | Face   | Partial Face Excavating Machines (PFM) | Various  | None or Grippers   | Rock Machines        |
|                 | None   | Full Face Rotating Cutting Head (TBM)  | Cutting disk<br>Cutting disk/<br>Cutting bits/<br>Cutting knives & teeth | Grippers<br>Thrust Jacks                                 |                      |
| Face and cavity | Shield | Mechanical                             | Cutting disk   | Grippers and Thrust Jacks                                | Soft Ground Machines |
|                 |        |  | Full Face Rotating Cutting Head (TBM)                                    | Thrust Jacks   |                      |
|                 |        | Compressed Air                         | Rod header/<br>Back hoe/<br>Manual excavation                            | Thrust Jacks   |                      |
|                 |        |  | PFM  | Thrust Jacks   |                      |
|                 |        | Fluid                                  | TBM  | Cutting bits/<br>Cutting knives & teeth                  |                      |
|                 |        |  | PFM  | Road header/Back hoe                                     |                      |
|                 |        | Earth Pressure Balance                 | TBM  | Cutting bits/Cutting knives & teeth                      |                      |
|                 |        |  | PFM  | Road header/Back hoe                                     |                      |
|                 |        | None or fluid                          | TBM  | Cutting disk/<br>Cutting bits/<br>Cutting knives & teeth |                      |
|                 |        |  | PFM  | Road header/Back hoe                                     |                      |

Barla & Pelizza (2000)



30 of 40


Tunnelling Grad Class (2012)

Dr. Erik Eberhardt



## TBM Excavation & Design

Single & Double Shield TBM's - Single-shield TBM's are cheaper and are the preferred machine for hard rock tunnelling. Double shielded TBMs are normally used in unstable geology (as they offer more worker protection), or where a high rate of advancement is required.



"Single" shield TBM



"Double" shield TBM



31 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## TBM Excavation & Design

### Impacts of Geotechnical Conditions on TBM Operations

| Major Geotechnical Conditions                            | Consequences/Requirements  |
|--|--|
| Loosening loads, blocky/slabby rock, overbreak, cave-ins | At the face: cutterhead jams, disc impact loading, cutter disc and mount damage possible, additional loss on available torque for cutting, entry to the face may be required with impact on equipment selection, recessed cutters may be recommended for face ground control.<br>In the tunnel: short stand-up time, delays for immediate and additional support (perhaps grouting, hand-mining), special equipment (perhaps machine modifications), gripper anchorage and steering difficulty, shut-down in extreme cases of face and crown instability. Extent of zones (perhaps with verification by advance sensing/probe hole drilling) may dictate shield required, and potential impact on lining type selection (as expanded segmental linings may not be reasonable), grouting, and backpacking time and costs may be high. |
| Groundwater inflow                                       | Low flow/low pressure - operating nuisance, slow-down, adequate pumping capability<br>high flow and/or high pressure - construction safety concerns, progress slow or shut-down, special procedures for support and water/wet muck handling, may require advance sensing/probe hole drilling.<br>Corrosive or high-salt water - treatment may be required before disposal, equipment damage, concrete reactivity, problems during facility operation.<br>Equipment modifications (as water-proofing) may be required if inflow is unanticipated - significant delays.  |



U.S. Army Corps of Engineers (1997)



32 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt



## TBM Excavation & Design

### Impacts of Geotechnical Conditions on TBM Operations

| Major Geotechnical Conditions                | Consequences/Requirements  |
|--|--|
| Squeezing ground                             | Shield stalling, must determine how extensive and how fast squeeze can develop, delays for immediate support, equipment modifications may be needed, if invert heave and train mucking - track repair and derail downtime.   |
| Ground gas/hazardous fluids/wastes           | Construction safety concerns, safe equipment more expensive, need increased ventilation capacity, delays for advance sensing/probing and perhaps project shut-down, special equipment modifications with great delays if unanticipated, muck management and disposal problems. |
| Overstress, spalls, bursts                   | Delays for immediate support, perhaps progress shut-down, construction safety concerns, special procedures may be required.  |
| Hard, abrasive rock                          | Reduced $PR_{av}$ and increased $F_p$ - TBM needs adequate installed capacities to achieve reasonable advance rates, delays for high cutter wear and cutterhead damage (especially if jointed/fractured), cutterhead fatigue, and potential bearing problems                   |
| Mixed-strength rock                          | Impact disc loading may increase failure rates, concern for side wall gripping problems with open shields, possible steering problems.   |
| Variable weathering, soil-like zones, faults | Slowed progress, if sidewall grippers not usable may need shield, immediate and additional support, potential for groundwater inflow, muck transport (handling and derralls) problems, steering difficulty, weathering particularly important in argillaceous rock.            |
| Weak rock at invert                          | Reduced utilization from poor traffickability, grade, and alignment - steering problems.   |

U.S. Army Corps of Engineers (1997)




33 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## TBM Excavation & Design



TBM working platform for installing support (e.g. rock bolts, meshing, shotcrete).



34 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## TBM Operation



35 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## TBM Excavation & Design - Pre-Cast Linings



36 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Tunnelling Breakthroughs



37 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## TBM Selection & Geological Risk

The Yacambú-Quibor Tunnel is a prime example of tunnelling blind - the geology was largely unfamiliar and unpredictable. With little previous experience, it was unknown how the rock would react, especially under the high stresses of the Andes.

**Geology:** Weak, tectonically sheared graphitic phyllites were encountered giving rise to serious squeezing problems, which without adequate support would result in complete closure of the tunnel.



**1975:** Excavation begins on the 24 km tunnel, for which the use of a full-face TBM is specified (for rapid excavation).

**1977:** The weak phyllites fail to provide the TBM grippers with enough of a foundation to push off of. Supporting squeezing ground was another defeating problem.

**1979:** During a holiday shutdown, squeezing rock conditions were left unchecked, resulting in the converging ground effectively "swallowing" one of the TBMs.

**1980's:** A decision is made to permit the tunnel to be excavated by drill & blast. Recently completed, it took more than 33 years to tunnel the full 24 km.



Mining out the remains of the trapped TBM.

Hoek (2001)



38 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt



## Sequential Excavation & Design - Benches

Bench excavations are used for large diameter tunnels in weak rock. The benefits are that the weak rock will be easier to control for a small opening and reinforcement can be progressively installed along the heading before benching downward. Variations may involve sequences in which the inverts, top heading and bench are excavated in different order.



39 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt

## Lecture References

Barla, G & Pelizza, S (2000). TBM Tunneling in difficult conditions. In *GeoEng2000, Melbourne*. Technomic Publishing Company: Lancaster, pp. 329-354.

Harding, H (1981). "Tunnelling: History and My Own Involvement". *Golden Associates*: Toronto, 258pp.

Hudson, JA & Harrison, JP (1997). "Engineering Rock Mechanics - An Introduction to the Principles". Elsevier Science: Oxford, 444pp.

Maidl, B, Herrenknecht, M & Anheuser, L (1996). "Mechanised Shield Tunnelling". Ernst & Sohn: Berlin, 428pp.

NTNU (1995). "Tunnel: Blast Design". Department of Building and Construction Engineering, Norwegian University of Science and Technology (NTNU), Trondheim, Project Report 2A-95.

NTNU-Anleggsdrift (1998). "Hard Rock Tunnel Boring: The Boring Process". Norwegian University of Science and Technology (NTNU), Trondheim, Project Report 1F-98.

Thuro, K & Plinninger, RJ (2003). Hard rock tunnel boring, cutting, drilling and blasting: rock parameters for excavatability. In: Proc., 10th ISRM Congress, Johannesburg. SAIMM: Johannesburg, pp. 1227-1234.

UNIT-NTH (1995). "Tunnel: Prognosis for Drill and Blast". Department of Building and Construction Engineering, Norwegian University of Science and Technology (NTNU), Trondheim, Project Report 2B-95.

Whittaker, BN & Frith, RC (1990). "Tunnelling: Design, Stability and Construction". Institution of Mining and Metallurgy: London, 460pp.



40 of 40

Tunnelling Grad Class (2012)

Dr. Erik Eberhardt